

AUTOMOTIVE MASKING TAPES

MT80

General Purpose Masking Tape

BACKING

Crepe paper

COLOUR

White

HEAT RESISTANCE

80 °C / 30 min

01 PRODUCT OVERVIEW

KEY FEATURES

- Medium adhesion on painted metal, rubber, glass or chrome
- Good holding power
- Clean removal
- Compatible with common water- and solvent-based paints
- Conforms to contours with masking paper or film
- Recommended for indoor operations

RECOMMENDED USE

General-purpose automotive masking tape for bodyshop masking and repair. Its crepe paper backing and balanced adhesive provide reliable hold and clean removal on painted metal, rubber, glass and chrome.

Suitable for curved profiles and for use with masking paper or protective film. Recommended for indoor paint operations.

02 TECHNICAL DATA

PROPERTY	TYPICAL VALUE	PROPERTY	TYPICAL VALUE
Backing	Crepe paper	Colour	White
Adhesive	Natural / synthetic rubber	Total thickness	150 µm
Tensile strength	65 N / 25 cm	Adhesion to steel	6 N / 25 mm
Elongation at break	10%	Temperature resistance	80 °C / 30 min
Paint compatibility	Water- and solvent-based	Recommended environment	Indoor operations

03 PRODUCT REFERENCES

PART	SIZE	PCS / CASE	BOX / PALLET
MT8048	48 mm × 50 m	18 rolls / case	120 boxes / pallet
MT8036	36 mm × 50 m	24 rolls / case	120 boxes / pallet
MT8024	24 mm × 50 m	36 rolls / case	120 boxes / pallet
MT8018	18 mm × 50 m	48 rolls / case	120 boxes / pallet

DATA STATUS

Values shown are typical averages and are not guaranteed minimum or maximum specification limits.

The information in this document is provided in good faith and is based on the supplied product data. Users must determine product suitability for the intended substrate, coating system, process conditions and removal time before use.